

nosnost (kg)	typ	vedení řetězu	zatřídění FEM / ISO	rychlost m/min	výška zdvihu (m)	velikost řetězu	max. hmotnost při výšce zdvihu	
							2,8	4,3
80	DCM-Pro 1	1/1	4m / M7	8,0/2,0	2,8 + 4,3	4,2x12,2	22	24
	DCM-Pro 2			16,0/4,0				
	DCM-Pro 5			24,0/6,0		5,3x15,2	28	30
125	DCM-Pro 1			8,0/2,0		4,2x12,2	22	24
	DCM-Pro 2			16,0/4,0				
	DCM-Pro 5			24,0/6,0		5,3x15,2	28	30
200	DCM-Pro 2		3m / M6	8,0/2,0		4,2x12,2	22	24
	DCM-Pro 5		4m / M7	16,0/4,0		5,3x15,2	28	30
250	DCM-Pro 2		2m+ / M5+	8,0/2,0		4,2x12,2	22	24
	DCM-Pro 5		4m / M7	16,0/4,0		5,3x15,2	28	30
315	DCM-Pro 5	4m / M7	8,0/2,0	5,3x15,2	37	38		
400	DCM-Pro 5	3m / M6						
500	DCM-Pro 5	2m+ / M5+						